

Transducer Signal Conditioning and Interface Modules

Features

- Accurate and repeatable
- LVDT and Half bridge Transducer Compatible
- Various Output Options
 - Voltage Outputs
 - Current Outputs (4-20mA)
 - TTL Outputs



Description

Solartron Metrology's range of conditioning electronics offers the user the ability to connect and configure LVDT and Half Bridge inductive sensors into an almost infinite number of combinations.

The range comprises the OD products which are housed in boxes in metal or plastic enclosures and can be easily mounted, the DRC conditioning module which is a DIN rail mount option, in line products such as the BICM and the ATM TTL converter which provides differential square wave signals perfect for simple PLC interfaces.

Customised or special products will always be considered when there is not an exact fit in our standard product range.

For optimum performance in terms of transducers and electronics please consider Solartron Metrology's Orbit[®]3 Digital Measurement System which out performs the conventional analogue LVDT and Half Bridge sensors in all aspects.

Precision. Quality. Reliability

www.solartronmetrology.com • sales.solartronmetrology@ametec.com

Transducer Signal Conditioning and Interface Modules

OD Series

The OD series of conditioning units is used to interface with Solartron's sensors to provide different functions to suit different applications.

The OD2 is a two wire 4-20 mA signal conditioner. It is designed for signal transmission over long distances due to low noise susceptibility.

The OD4 (OD5 is a mains powered equivalent) is powered from a single 10 to 30V DC supply. The outputs are fully adjustable for offset and gain.



DRC

The DRC is a DIN rail mounted version of the OD4



ATM TTL Converter TTL RS422 is one of the most commonly used methods of communicating between Linear displacement sensors and Control or data Acquisition systems. Most sensors which offer this are incremental sensors and can loose position if moved to quickly. Solartron's ATM is an absolute system and can never loose position even if power is interrupted



BICM In Line Module

The BICM provides a simple low cost in line conditioning unit. This is ideal when the transducer set up is unlikely to require adjustment. The design is robust for harsh environments. An IP67 version is available



Technical Specifications

Power Requirement

	OD2	OD4	OD5	DRC	BICM	
Input Voltage VDC	13-42	10-30	N/A	10-30V	±15	24
Input Voltage VAC	N/A	N/A	90-264	N/A	N/A	N/A
Input Current (mA)	<30	140 at 10V 50 at 30V	250	160 at 10V 70 at 30V	±12	24
Frequency (Hz)	N/A	N/A	47-63	N/A	N/A	N/A

Transducer Interface

Primary voltage (Vrms)	0-9		3		1.2 – 21	
Primary frequency (kHz)	5 or 13	2.5 or 5		5,10 or 13	2.5 to 20	
Input Range	30-530mV/V ¹		55 to 5000mV		up to 3.5	
Input Load (kΩ)	2	2, 10, 100		2, 100	100	
Options	Forward and reverse			see note 2		

Output

Voltage Output VDC		Up to ±10			
Current Output mA	4-20	Up to ±20 into 150Ω load			
Output Ripple	<38μA rms	<1 mV rms		<14 mV rms	
Output Offset	Up to 100% on maximum gain (coarse and fine adjustment)				
Temperature Coefficient Gain (%FSO/°C)		<0.01		<0.03	
Temperature Coefficient Offset (%FSO/°C)		<0.01		<0.02	
Warm Up (minutes)	15 minutes				
Linearity (%FSO)	<0.02			<0.1	
Bandwidth (-3dB) (Hz)	25	500Hz, 1kHz			

Environmental (Note 3)

Storage Temperature	-40 to +80	-20 to +80		-20 to +80		
Operating Temperature	0 to +60					
IP rating	65	40	40	None	40/67	40

Mechanical


Transducer Connections	Terminals	Din Connector	Terminals	Solder tag or factory fit for IP67		
Power connections	Terminals	IEC320 C14				
Weight	ABS	Painted Aluminium Box	Plastic	Plastic or		
Material				DIN rail	In line	
Mounting						

Note 1: For transducers with sensitivity > 250mV/V, an adjustable attenuator is required- contact sales

Note 2; Transducer is connected via external screw terminal user can therefore configure options

Note 3: For higher environmental levels(and other custom options) contact sales office

ATM Module: TTL Compatible Conditioning Unit that WILL NOT loose count when the sensor is moved quickly unlike incremental sensors. 500kHz Output rate



Technical Specification

Measurement

Transducer types	All Solartron Displacement Transducers
Accuracy (%FSO)	<0.25
Resolution (x4 interpolation)	0.1
Repeatability	transducer dependent

Electrical

Power	+5 ±0.25 VDC @ 100 mA
Output Signal	A and B, /A and /B TTL square waves RS422 levels
Output frequency (kHz)	50, 100, 125, 250, & 500 (factory selectable)
Bandwidth	100 Hz

Environmental (electronics)

Sealing	IP43
Operating temperature (°C)	0 to +60
Storage temperature (°C)	-20 to +70

Refer to product manual 502724 for details of operation – contact sales office/web site

For 3D drawings, please contact sales.solartronmetrology@ametek.co.uk

United Kingdom - Head Office

Solartron Metrology
Steyning Way
Bognor Regis
West Sussex
PO22 9ST
Tel: +44 (0) 1243 833333
Fax: +44 (0) 1243 833322
Sales.solartronmetrology@ametek.com

France

Solartron Metrology
Rond-point de l'Espine des Champs
Buroplus - Bat. D
Elancourt 78990
Tel: +33 (0)1 30 68 89 50
Fax: +33 (0)1 30 68 89 59
france.solartronmetrology@ametek.com

Germany

Ametek GmbH
Solartron Metrology Division
Rudolf-Diesel-Strasse 16
40670 Meerbusch
Tel: +49 (0) 2159 9136 500
Fax: +49 (0) 2159 9136 505
vertrieb.solartron@ametek.de

Brazil

Ametek do Brasil, Ltda
Rod. Eng Ermenio de Oliveira Penteado, Km 57, SP75
Bairro Tombadouro
13337-300, Indaiatuba, SP, Brazil
Tel: +55 19 2107 4126

India

Ametek Instruments India Private Limited
1st Floor, Left Wing
Prestige Featherlite Tech Park
Plot #148, EPIP II Phase
Whitefield, Bengaluru 560 066
Karnataka, India
Tel: +91 80 6782 3200
Fax: +91 80 6782 3232

USA

Solartron Metrology
USA Central Sales Office
915 N.New Hope Road, Suite C
Gastonia, NC 28054
Tel: +1 800 873 5838
Fax: +1 704 868 8466
usasales.solartronmetrology@ametek.com

China

AMETEK Commercial Enterprise (Shanghai) Co. Ltd
No. 155 Puhui Road
Ju Ting Economic Development Zone
Shanghai 200131, China
Tel: +86 21 5763 2509
Fax: +86 21 5866 0969 Ext. 261/262
china.solartronmetrology@ametek.com



**Solartron
Metrology**

Precision Driven

Offices worldwide
Agent and distributor details
available at
www.solartronmetrology.com



Q09540

Solartron pursues a policy of continuous development. Specifications in this document may therefore be changed without notice.

AMETEK[®]
ULTRA PRECISION TECHNOLOGIES

Precision. Quality. Reliability

www.solartronmetrology.com • sales.solartronmetrology@ametek.com